

Please provide the following information, and submit to the NOAA DM Plan Repository.

Reference to Master DM Plan (if applicable)

As stated in Section IV, Requirement 1.3, DM Plans may be hierarchical. If this DM Plan inherits provisions from a higher-level DM Plan already submitted to the Repository, then this more-specific Plan only needs to provide information that differs from what was provided in the Master DM Plan.

URL of higher-level DM Plan (if any) as submitted to DM Plan Repository:

1. General Description of Data to be Managed**1.1. Name of the Data, data collection Project, or data-producing Program:**

2013 NOAA Coastal California TopoBathy Merge Project

1.2. Summary description of the data:

This project merged recently collected topographic, bathymetric, and acoustic elevation data along the entire California coastline from approximately the 10 meter elevation contour out to California's 3 mile state water's boundary. Topographic LiDAR: The topographic lidar data used in this merged project was the 2009-2011 CA Coastal Conservancy Lidar Project. The data were collected between October 2009 and August 2011. This collection was a joint effort by the NOAA Office for Coastal Management (OCM); the California State Coastal Conservancy (SCC) Ocean Protection Council (OPC); Scripps Institution of Oceanography; and the Joint Airborne Lidar Bathymetry Technical Center of Expertise (JALBTCX). The data coverage extends landward 500 m from the shoreline, along the entire California coastline. The LAS classifications are as follows: 1-Unclassified, 2-Ground, 7-Noise, 9-Water, 10- Mudflats, 12-Overlap. The LAS points were manually re-classified from water and unclassified to ground in offshore areas where necessary. Bathymetric LiDAR: The bathymetric lidar data used in this merged project was 2009-2010 U.S. Army Corps of Engineers (USACE) Joint Airborne Lidar Bathymetry Center of Expertise (JALBTCX) lidar, provided by JALBTCX. The data were collected for the California Coastal Mapping Project (CCMP). The original data were in ASCII format and were converted to LAS v1.2. The LAS data were classified as follows: 21-Non-submerged Bathymetry, 22-Bathymetry, 23-Ignored Submerged Bathymetry/Overlap. Multibeam Acoustic Data: The acoustic data data used in this merged project were provided by the California Seafloor Mapping Program (CSMP) Ocean Protection Council and NOAA's National Geophysical Data Center (NGDC). The original data were in ASCII format and were converted to LAS v1.2. NOAA's VDatum software was used to vertically transform soundings from mean lower low water (MLLW) tidal datum to NAVD88 orthometric datum where necessary. The LAS data were classified as follows: 25-Submerged Acoustic, 26-Ignored Submerged Acoustic/Overlap. Upon receipt of the data, the NOAA Office for Coastal Management (OCM) converted some of the classifications for data storage and Digital Coast provisioning purposes. The following are the classifications of data available from the NOAA Digital Coast: 1 - Unclassified, 2 - Ground,

7 - Low point (noise), 9 - Water, 11 - Bathymetry, 12 - Overlap, 13 - Submerged Acoustic, 14 - Non-Submerged Bathymetry, 15 - Ignored Submerged Bathymetry/Overlap, 16 - Ignored Submerged Acoustic/Overlap

Original contact information:

Contact Org: NOAA Office for Coastal Management

Phone: 843-740-1202

Email: coastal.info@noaa.gov

1.3. Is this a one-time data collection, or an ongoing series of measurements?

One-time data collection

1.4. Actual or planned temporal coverage of the data:

2013-10-30

1.5. Actual or planned geographic coverage of the data:

W: -124.535124, E: -117.047904, N: 42.012734, S: 32.525255

1.6. Type(s) of data:

(e.g., digital numeric data, imagery, photographs, video, audio, database, tabular data, etc.)

1.7. Data collection method(s):

(e.g., satellite, airplane, unmanned aerial system, radar, weather station, moored buoy, research vessel, autonomous underwater vehicle, animal tagging, manual surveys, enforcement activities, numerical model, etc.)

1.8. If data are from a NOAA Observing System of Record, indicate name of system:

1.8.1. If data are from another observing system, please specify:

2. Point of Contact for this Data Management Plan (author or maintainer)

2.1. Name:

NOAA Office for Coastal Management (NOAA/OCM)

2.2. Title:

Metadata Contact

2.3. Affiliation or facility:

NOAA Office for Coastal Management (NOAA/OCM)

2.4. E-mail address:

coastal.info@noaa.gov

2.5. Phone number:

(843) 740-1202

3. Responsible Party for Data Management

Program Managers, or their designee, shall be responsible for assuring the proper management of the data produced by their Program. Please indicate the responsible party below.

3.1. Name:

3.2. Title:

Data Steward

4. Resources

Programs must identify resources within their own budget for managing the data they produce.

4.1. Have resources for management of these data been identified?

4.2. Approximate percentage of the budget for these data devoted to data management (specify percentage or "unknown"):

5. Data Lineage and Quality

NOAA has issued Information Quality Guidelines for ensuring and maximizing the quality, objectivity, utility, and integrity of information which it disseminates.

5.1. Processing workflow of the data from collection or acquisition to making it publicly accessible

(describe or provide URL of description):

Process Steps:

- 2012-12-14 00:00:00 - All data were imported into GeoCue software, converted to LAS v1.2, and transformed, if necessary, to UTM coordinate system, zone 10 North, meters, horizontal datum NAD83 (NSRS2007), vertical datum NAVD88, Geoid 09, meters. Each data type (topographic, bathymetric, and acoustic) were then tiled individually according to project specifications (1500m x 1500m). Data for the NOAA Coastal California Data Merge Project were provided by various sources. Topographic data were provided by NOAA in LAS format, collected for the California Coastal Mapping Project (CCMP). The topographic data were provided with the following classifications: Class 1 = Unclassified (This class includes vegetation, buildings, noise etc.), Class 2 = Ground, Class 7 = Noise, Class 9 = Water, Class 10 = Mudflats, Class 12 = Overlap. Bathymetric data were provided by Joint Airborne Bathymetry LiDAR Technical Center of Expertise (JALBTCX) in ASCII format, collected for the National Coastal Mapping Program (NCMP) in 2009. Initial bathymetric data were classified in GeoCue to Class 22 = Submerged bathymetry. Multibeam acoustic data were downloaded from the California Seafloor Mapping Program: Ocean Protection Council (CSMP) (<http://seafloor.csumb.edu/SFMLwebDATA.htm>), and from NOAA's NGDC (<http://maps.ngdc.noaa.gov/viewers/>

bathymetry/) in ASCII formats, or from USGS open file reports where available. NOAA's VDatum software (version 2.3.5) was used to vertically transform soundings from mean lower low water (MLLW) tidal datum to NAVD88 orthometric datum where necessary.

- 2013-04-12 00:00:00 - Reclassification of Topographic data: Reclassification of offshore islands and pinnacles was a critical component to the success of the final merged product. Tiles within 100m of the coastal shoreline were selected for review and manual classification. Each tile was brought into TerraScan and a temporary surface model was created from the topographic ground points (class 2). Using aerial imagery as a guide, the coastline was examined for any exposed islands that may be incorrectly classified as water in the LAS. Once located, points were reclassified from water (class 9) to ground (class 2) or from unclassified (class 1) to ground. Date for this process step is 20130201-20130412.

- 2013-05-10 00:00:00 - Topographic-Bathymetric Seamline: All breaklines provided by NOAA were merged into a single polygon feature class. This became the foundation of the initial seamline. Areas containing both topographic and bathymetric data along the coastline were reviewed on a tile-by-tile basis using difference rasters. Because the topographic data had better horizontal resolution and vertical accuracy than the bathymetric data, it generally took priority over bathymetric data in overlap areas. However, a smoother transition between the topographic and bathymetric LiDAR datasets may be achieved by modifying the extent of the topographic data in favor of the bathymetric data. In these cases, the breakline was adjusted accordingly. The final polygon feature class was used for reclassification of LAS points in TerraScan. The polygon was converted to a polyline in Arc and clipped to the extent of the coastal shoreline. This final polyline was used as basis for the creation of the DEM smoothing buffers. Date for this process step is 20130222-20130510.

- 2013-02-19 00:00:00 - Acoustic-Acoustic Seamline (Production Block 2b): In surveys with multiple resolutions, the best available resolution data was prioritized and reclassified using TerraScan software. A best fit line was not produced. Between surveys, a best fit line was generated by creating difference rasters and manually digitizing a new boundary.

- 2013-06-21 00:00:00 - Acoustic-Acoustic Seamline (Production Blocks 3 and 4): In bathymetric attributed grid (BAG) surveys with multiple resolutions, the best available resolution data was prioritized and reclassified using TerraScan software. A best fit line was not produced. Between unique surveys, a best fit line was generated by creating difference rasters and manually digitizing a new boundary along areas with minimal offset. Date for this process setp 20130501-20130621.

- 2013-02-27 00:00:00 - Bathymetric-Acoustic Seamline (Production Block 2b): The bathymetric-acoustic seamline was generated using the same methodology as the acoustic overlap seamline. The final polyline was used as basis for the creation of the DEM smoothing buffers.

- 2013-06-21 00:00:00 - Bathymetric-Acoustic Seamline (Production Blocks 3 and 4): The bathymetric-acoustic seamline was generated using the same methodology as

the acoustic overlap seamline, using difference rasters and manually digitizing seamlines with minimal offset. The final polyline was used as basis for the creation of the DEM smoothing buffers. The date for this process step is 20130501-20130621.

- 2013-05-17 00:00:00 - Reclassification of Bathymetric data: In areas of overlap where topographic data were given priority over bathymetric data, overlapping bathymetric points were moved to class 21 (non-submerged bathymetry). This was performed in TerraScan using the final seamline polygon. A minimum of three (3) data points within a 15m meter radius is required for inclusion in the DEM. An extent polygon is needed to accomplish this task. Topographic ground points (class 2) and bathymetric points (class 22) were converted to a masspoint feature class in Arc. The masspoints were used as the input in the Aggregate Points tool in Arc with a set distance of 15m. After the final extent polygons were generated, class 22 bathymetric points not within these polygons were moved to class 23 in TerraScan. Points outside the extent polygon remained in class 21/22. Finally, to remove above-ground artifacts from the bathymetric data, all class 22 points with elevations above +1m were reassigned to class 21 using an automated process in TerraScan. This removed docks, piers, bridges, and other miscellaneous artifacts from the point cloud. Bathymetric data between 0-1m elevation were left in class 22 to avoid classifying out too many data points in the nearshore areas. Bathymetric elevations between 0-1m were evaluated on a tile-by-tile basis and moved to class 21 if necessary. The date for this process step is 20130304-20130517.
- 2013-03-06 00:00:00 - Reclassification of Acoustic data (Production Block 2b): Each area of the acoustic data was reclassified from the temporary class codes to the final class 25 (submerged multibeam acoustic) and class 26 (acoustic overlap) designations using the polygons generated from the acoustic-acoustic seamline boundaries. Best resolution data was prioritized in multi-resolution surveys. Best fit seamline was used between surveys.
- 2013-06-21 00:00:00 - Reclassification of Acoustic data (Production Blocks 3 and 4): Each area of the acoustic data was reclassified from the temporary class codes to the final class 25 (submerged multibeam acoustic) and class 26 (acoustic overlap) designations. Voids in high resolution acoustic BAG data were filled with available lower resolution BAG data for each acoustic data set. This is an automated process using Fugro proprietary software specially developed for this project. This process results in a merged LAS point cloud for each survey location utilizing the best resolution BAG data. The ignored points were classified as class 26. The same filling process was used in case of NCCMP data for survey locations where data of various acquisition dates were available within a survey. Priority was given to data collected in 2010, following by 2008 and older datasets. Surface subtraction images were generated and utilized to digitize best fit line between overlapping acoustic project data sets. Overlapping acoustic datasets were reclassified and merged based on the best fit line using LAS mosaic software developed by Fugro. The merged point cloud data for each acoustic project was tiled to the project required tiling scheme. The date for this process step is 20130501-20130621.
- 2013-03-06 00:00:00 - Reclassification of Bathymetric data (Production Block 2b): In

overlapping areas between acoustic and bathymetric datasets, priority was given to the acoustic dataset due to more efficient coverage and higher resolution where available. With exception of two instances where best fit line was used, the bathymetric-acoustic seamline was represented by geographic extent of class 25. The bathymetric data within this extent was reclassified to class 23.

- 2013-06-21 00:00:00 - Reclassification of Bathymetric data (Production Blocks 3 and 4): In overlapping areas between acoustic and bathymetric datasets, priority was given to the acoustic dataset due to more efficient coverage and higher resolution where available. With exception of two instances where best fit line was used, the bathymetric-acoustic seamline was represented by geographic extent of class 25. The bathymetric data within this extent was reclassified to class 23. Acoustic point cloud and bathymetric lidar data were merged using TSCAN project. The date for this process step is 20130501-20130621.

- 2013-01-01 00:00:00 - The NOAA Office for Coastal Management (OCM) received the files in LAS format 1.2. The horizontal datum was NAD83 NSRS2007. The vertical datum was NAVD88. The coordinate system was UTM Zones 10 and 11 North. The horizontal and vertical units were in meters and the Geoid model was Geoid 09. OCM performed the following processing for data storage and Digital Coast provisioning purposes: 1. The data were converted from NAVD88 elevations to GRS80 (ellipsoid) elevations using Geoid 09.2. The data were converted from UTM Zones 10 and 11 North coordinates to geographic coordinates. 3. Elevation outliers were filtered. 4. Re-classing of the following: points that were classed as 10 (mudflats) were changed to 2 (ground), points that were classed as 21 (non-submerged bathymetry) were changed to 14 (non-submerged bathymetry), points that were classed as 22 (bathymetry) were changed to 11 (bathymetry), points that were classed as 23 (ignored submerged bathymetry/overlap) were changed to 15 (ignored submerged bathymetry/overlap), points that were classed as 25 (submerged acoustic) were changed to 13 (submerged acoustic), points that were classed as 26 (ignored multibeam acoustic/overlap) were changed to 16 (ignored multibeam acoustic/overlap). 5. The data were zipped (compressed).

5.1.1. If data at different stages of the workflow, or products derived from these data, are subject to a separate data management plan, provide reference to other plan:

5.2. Quality control procedures employed (describe or provide URL of description):

6. Data Documentation

The EDMC Data Documentation Procedural Directive requires that NOAA data be well documented, specifies the use of ISO 19115 and related standards for documentation of new data, and provides links to resources and tools for metadata creation and validation.

6.1. Does metadata comply with EDMC Data Documentation directive?

No

6.1.1. If metadata are non-existent or non-compliant, please explain:

Missing/invalid information:

- 1.6. Type(s) of data
- 1.7. Data collection method(s)
- 3.1. Responsible Party for Data Management
- 4.1. Have resources for management of these data been identified?
- 4.2. Approximate percentage of the budget for these data devoted to data management
- 5.2. Quality control procedures employed
- 7.1. Do these data comply with the Data Access directive?
 - 7.1.1. If data are not available or has limitations, has a Waiver been filed?
 - 7.1.2. If there are limitations to data access, describe how data are protected
- 7.4. Approximate delay between data collection and dissemination
- 8.1. Actual or planned long-term data archive location
- 8.3. Approximate delay between data collection and submission to an archive facility
- 8.4. How will the data be protected from accidental or malicious modification or deletion prior to receipt by the archive?

6.2. Name of organization or facility providing metadata hosting:

NMFS Office of Science and Technology

6.2.1. If service is needed for metadata hosting, please indicate:

6.3. URL of metadata folder or data catalog, if known:

<https://www.fisheries.noaa.gov/inport/item/49649>

6.4. Process for producing and maintaining metadata

(describe or provide URL of description):

Metadata produced and maintained in accordance with the NOAA Data Documentation Procedural Directive: https://nosc.noaa.gov/EDMC/DAARWG/docs/EDMC_PD-Data_Documentation_v1.pdf

7. Data Access

NAO 212-15 states that access to environmental data may only be restricted when distribution is explicitly limited by law, regulation, policy (such as those applicable to personally identifiable information or protected critical infrastructure information or proprietary trade information) or by security requirements. The EDMC Data Access Procedural Directive contains specific guidance, recommends the use of open-standard, interoperable, non-proprietary web services, provides information about resources and tools to enable data access, and includes a Waiver to be submitted to justify any approach other than full, unrestricted public access.

7.1. Do these data comply with the Data Access directive?

7.1.1. If the data are not to be made available to the public at all, or with limitations, has a Waiver (Appendix A of Data Access directive) been filed?

7.1.2. If there are limitations to public data access, describe how data are protected from unauthorized access or disclosure:

7.2. Name of organization of facility providing data access:

NOAA Office for Coastal Management (NOAA/OCM)

7.2.1. If data hosting service is needed, please indicate:

7.2.2. URL of data access service, if known:

<https://coast.noaa.gov/dataviewer/#/lidar/search/where:ID=2612>

https://coast.noaa.gov/htdata/lidar1_z/geoid18/data/2612

7.3. Data access methods or services offered:

This data can be obtained on-line at the following URL:<https://coast.noaa.gov/dataviewer/#/lidar/search/where:ID=2612> This data set is dynamically generated based on user-specified parameters.;

7.4. Approximate delay between data collection and dissemination:

7.4.1. If delay is longer than latency of automated processing, indicate under what authority data access is delayed:

8. Data Preservation and Protection

The NOAA Procedure for Scientific Records Appraisal and Archive Approval describes how to identify, appraise and decide what scientific records are to be preserved in a NOAA archive.

8.1. Actual or planned long-term data archive location:

(Specify NCEI-MD, NCEI-CO, NCEI-NC, NCEI-MS, World Data Center (WDC) facility, Other, To Be Determined, Unable to Archive, or No Archiving Intended)

8.1.1. If World Data Center or Other, specify:

8.1.2. If To Be Determined, Unable to Archive or No Archiving Intended, explain:

8.2. Data storage facility prior to being sent to an archive facility (if any):

Office for Coastal Management - Charleston, SC

8.3. Approximate delay between data collection and submission to an archive facility:

8.4. How will the data be protected from accidental or malicious modification or deletion prior to receipt by the archive?

Discuss data back-up, disaster recovery/contingency planning, and off-site data storage relevant to the data collection

9. Additional Line Office or Staff Office Questions

Line and Staff Offices may extend this template by inserting additional questions in this section.